

Quality Checklist

Aleph Objects, Inc. ◆ 626 West 66th Street ◆ Loveland, Colorado 80538 USA

+1-970-377-1111 • www.alephobjects.com • www.lulzbot.com

Model: TAZ 4.0 3D Printer			
MOGCI. IAZ 4.0 3D FIIIICI			
Serial Number:			
Date Checked:			
Checked by:			
General			
☐ Are all the screws and zip ties tight?			
☐ Are the X and Y axis square to each other?			
Are the gaps at the ends of the extrusion closed?			
Are all the parts flush and straight to the edges with clean lines?			
☐ Are the current version of parts being used?			
Verify that the following are mounted correctly:			
 Feed tube, tube on back side of mount 			
2. Spool Arm, correct height			
3. Double bearing on carriage, step side towards X motor			
4. Finger clip, taller side on left			
☐ Are the switches tight? They shouldn't wiggle side to side.			
☐ Are all 8 rubber feet installed?			
☐ Is the PET tape free of bubbles and wrinkles?			
Is the heat bed adhesive smooth and consistent with no finger prints?Does the extruder mount have 4 unused inserts on the sides?			
☐ Does filament slide through the feed tube?			
Y Axis			
☐ Does the Y bed move freely back and forth?			
☐ Is the Y bed tight side to side from motion and twisting?			
☐ Are all the screws on the bearing holders tight?			



Quality Checklist

Aleph Objects, Inc. • 626 West 66th Street • Loveland, Colorado 80538 USA

+1-970-377-1111 • www.alephobjects.com • www.lulzbot.com

	Does the Y belt rub the bottom of the y-idler by the bearings? Is the Y pulley tight? Is one of the set screws on the Y pulley aligned with the flat on the motor shaft? Are both pulley set screws tightened? Is the level of the Y pulley at the same height as where the belt mounts on the belt holder? Is the Y belt tight? Are the bed leveling springs/posts in the correct place? Are all the Y mounting brackets flush and tight? Are the belts trimmed far enough to not interfere with the pulley or bearing?	
	Is the X pulley tight? Is one of the set screws on the X pulley aligned with the flat on the motor shaft? Are both pulley set screws tightened? Is the belt free from rubbing anywhere during motion? Is the X belt tight? Does the X axis move freely end to end? Are the X bars flush with the left side? Are the set screws that hold the X bars tight? Are the belts trimmed far enough to not interfere with the pulley or bearing?	
Z Axis		
	Is the Z adjuster vertical? Do the Z drive rods rotate smoothly with no up and down movement between the bearings? Are the 4 Z coupler set screws tight and aligned with flats on the drive rods and motors? Are the Z smooth rods flush with the top plate?	



Quality Checklist

Aleph Objects, Inc. ◆ 626 West 66th Street ◆ Loveland, Colorado 80538 USA

+1-970-377-1111 • www.alephobjects.com • www.lulzbot.com

Extruder		
	Can you adjust the extruder springs?	
	Are the V grooves on the extruder gears lined up?	
	Is the extruder mount secure on the x-carriage?	
	Does the idler bearing stick out of the idler block?	
	Is the hobbing aligned to the hole in the extruder?	
	Is the set screw in the small gear tight and on the flat of the motor shaft?	
	Can you feed filament about 115mm from the top of the extruder?	
	Are the gears tight with no back-lash?	
	Do the extruder gears turn smoothly for several rotations?	
Electronics		
	Are the D-Sub connector screws tight?	
	Are the LCD connectors in the correct position and pressed in firmly?	
	Are the 14 Pos. connectors tight and in the correct position?	
	Can you plug in USB cable from the outside of the enclosure?	

☐ Is the plug cover for second extruder installed?

☐ Are the screws that fasten the control box to the frame tight?