

# **Material Safety Data Sheet**

# **Americas Styrenics LLC**

Product Name: STYRON\* 487 Natural Polystyrene Issue Date: 2014.03.25 **Print Date: 2014.6.6** 

Americas Styrenics LLC encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

# **Product and Company Identification**

#### **Product Name**

STYRON\* 487 Natural Polystyrene

### **COMPANY IDENTIFICATION**

Americas Styrenics LLC **Suite 1200** 24 Waterway Avenue The Woodlands, TX 77380 **United States** 

For MSDS updates and Product Information: 888-552-6789

Prepared By: Prepared for use in Canada by EH&S, Product Regulatory

Management Department.

450-652-1029

Revision 2014.03.25 **Print Date:** 6/6/2014

**Customer Information Number:** 844-512-1212

PSCS@amsty.com

#### **EMERGENCY TELEPHONE NUMBER**

24-Hour Emergency Contact: 800-424-9300 **Local Emergency Contact:** 800-510-8510

#### 2. **Hazards Identification**

**Emergency Overview** 

Color: Natural

Physical State: Pellets or Granules

Odor: Odorless to mild **Hazards of product:** 

Slipping hazard.

Styron ®(TM) is a registered trademark of Styron LLC.

## **Potential Health Effects**

**Eye Contact:** Solid or dust may cause irritation or corneal injury due to mechanical action. Elevated temperatures may generate vapor levels sufficient to cause eye irritation. Effects may include discomfort and redness.

**Issue Date: 2014.03.25** 

**Skin Contact:** Prolonged contact is essentially nonirritating to skin. Mechanical injury only. Under normal processing conditions, material is heated to elevated temperatures; contact with the material may cause thermal burns.

**Skin Absorption:** No adverse effects anticipated by skin absorption.

**Inhalation:** No adverse effects are anticipated from single exposure to dust. Vapors/fumes released during thermal processing may cause respiratory irritation.

**Ingestion:** Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts. May cause choking if swallowed.

# 3. Composition/information on ingredients

Component	CAS#	Amount W/W
Styrene, 1,3-butadiene copolymer	9003-55-8	>= 94.0 %
Copolymer mixture	Trade secret	<= 5.0 %

Amounts are presented as percentages by weight.

# 4. First-aid measures

**Eye Contact:** If irritation occurs, Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**Skin Contact:** If molten material comes in contact with the skin, do not apply ice but cool under ice water or running stream of water. DO NOT attempt to remove the material from skin. Removal could result in severe tissue damage. Seek first aid or medical attention as needed.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

**Ingestion:** If swallowed, seek medical attention. May cause gastrointestinal blockage. Do not give laxatives. Do not induce vomiting unless directed to do so by medical personnel.

**Notes to Physician:** If burn is present, treat as any thermal burn, after decontamination. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

# 5. Fire Fighting Measures

**Extinguishing Media:** Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam.

**Fire Fighting Procedures:** Keep people away. Isolate fire and deny unnecessary entry. Soak thoroughly with water to cool and prevent re-ignition. If material is molten, do not apply direct water stream. Use fine water spray or foam. Cool surroundings with water to localize fire zone. Hand held dry chemical or carbon dioxide extinguishers may be used for small fires.

**Special Protective Equipment for Firefighters:** Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

**Product Name:** STYRON\* 487 Natural Polystyrene

**Unusual Fire and Explosion Hazards:** Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Dense smoke is produced when product burns.

**Issue Date: 2014.03.25** 

**Hazardous Combustion Products:** During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon dioxide. Carbon monoxide.

See Section 9 for related Physical Properties

# 6. Accidental Release Measures

**Steps to be Taken if Material is Released or Spilled:** Sweep up. Recover spilled material if possible. Collect in suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

**Personal Precautions:** Keep unnecessary and unprotected personnel from entering the area. Spilled material may cause a slipping hazard. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

**Environmental Precautions:** Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

# 7. Handling and Storage

## Handling

General Handling: No smoking, open flames or sources of ignition in handling and storage area. Good housekeeping and controlling of dusts are necessary for safe handling of product. Avoid breathing process fumes. Use with adequate ventilation. When appropriate, unique handling information for containers can be found on the product label. Workers should be protected from the possibility of contact with molten resin. Do not get molten material in eyes, on skin or clothing. Keep away from heat, sparks and flame. Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, electrically bond and ground equipment and do not permit dust to accumulate. Dust can be ignited by static discharge.

## Storage

Store in a dry place. Store in accordance with good manufacturing practices.

# 8. Exposure Controls / Personal Protection

#### **Exposure Limits**

Consult local authorities for recommended exposure limits. None established

## **Personal Protection**

**Eye/Face Protection:** Use safety glasses. If there is a potential for exposure to particles which could cause eye discomfort, wear chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin Protection: No precautions other than clean body-covering clothing should be needed.

Hand protection: Chemical protective gloves should not be needed when handling this material. Consistent with general hygienic practice for any material, skin contact should be minimized. Use gloves with insulation for thermal protection, when needed. Use gloves to protect from mechanical injury. Selection of gloves will depend on the task.

**Respiratory Protection:** Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. Use an

approved air-purifying respirator when vapors are generated at increased temperatures or when dust or mist is present. The following should be effective types of air-purifying respirators: When dust/mist are present use a/an Particulate filter. When combinations of vapors, acids, or dusts/mists are present use a/an Organic vapor cartridge with a particulate pre-filter.

**Issue Date: 2014.03.25** 

**Ingestion:** Use good personal hygiene. Do not consume or store food in the work area. Wash hands before smoking or eating.

# **Engineering Controls**

**Ventilation:** Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

# 9. Physical and Chemical Properties

Physical State Pellets or Granules

**Color** Natural

Odor Odorless to mild Flash Point - Closed Cup Not applicable

Flammable Limits In Air Lower: Not applicable

Upper: Not applicable

Autoignition Temperature No test data available Vapor Pressure Not applicable

Boiling Point (760 mmHg)
Vapor Density (air = 1)
Not applicable
Not applicable

Specific Gravity (H2O = 1) 1.04 - 1.06 Estimated
Freezing Point Not applicable

Melting Point No test data available

Solubility in Water (by Negligible

weight)

pH Not applicableDecomposition No test data available

Temperature

Partition coefficient, n-

octanol/water (log Pow)

No data available for this product.

Kinematic Viscosity Not applicable

# 10. Stability and Reactivity

#### Stability/Instability

Stable under recommended storage conditions. See Storage, Section 7.

**Conditions to Avoid:** Avoid temperatures above 300 °C. Exposure to elevated temperatures can cause product to decompose.

Incompatible Materials: None known.

### **Hazardous Polymerization**

Will not occur.

# **Thermal Decomposition**

Decomposition products depend upon temperature, air supply and the presence of other materials. Processing may release fumes and other decomposition products. At temperatures exceeding melt temperatures, polymer fragments can be released. Fumes can be irritating. Decomposition products can include and are not limited to: Combustible gases.

# 11. Toxicological Information

# **Acute Toxicity**

## Ingestion

Single dose oral LD50 has not been determined.

Typical for this family of materials. Estimated LD50, Rat > 5,000 mg/kg

### **Skin Absorption**

The dermal LD50 has not been determined.

Typical for this family of materials. Estimated LD50, Rabbit > 2,000 mg/kg

#### Inhalation

The LC50 has not been determined.

### **Repeated Dose Toxicity**

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

# **Chronic Toxicity and Carcinogenicity**

No relevant information found.

### **Developmental Toxicity**

No relevant information found.

#### **Reproductive Toxicity**

No relevant information found.

## **Genetic Toxicology**

No relevant information found.

# 12. Ecological Information

# **ENVIRONMENTAL FATE**

# **Movement & Partitioning**

No bioconcentration of the polymeric component is expected because of its high molecular weight. In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material will sink and remain in the sediment.

## Persistence and Degradability

This water-insoluble polymeric solid is expected to be inert in the environment. Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

#### **ECOTOXICITY**

Not expected to be acutely toxic, but material in pellet or bead form may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

# 13. Disposal Considerations

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device.

**Page** 5 of 7

**Issue Date: 2014.03.25** 

**Product Name:** STYRON\* 487 Natural Polystyrene **Issue Date:** 2014.03.25

# 14. Transport Information

#### **TDG Small container**

**NOT REGULATED** 

# **TDG Large container**

NOT REGULATED

#### **IMDG**

**NOT REGULATED** 

### ICAO/IATA

**NOT REGULATED** 

# 15. Regulatory Information

#### **US. Toxic Substances Control Act**

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30

## **CEPA - Domestic Substances List (DSL)**

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

## **Hazardous Products Act Information: CPR Compliance**

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

#### Hazardous Products Act Information: WHMIS Classification

This product is not a "Controlled Product" under WHMIS.

# 16. Other Information

# **Product Literature**

Additional information on this product may be obtained by calling your sales or customer service contact.

# **Recommended Uses and Restrictions**

A polystyrene plastic - For industrial conversion as a raw material for manufacture of articles or goods. We recommend that you use this product in a manner consistent with the listed use. If your intended use is not consistent with the stated use, please contact your sales or technical service representative.

## Revision

Identification Number: 81286 / 1004 / Issue Date 2014.03.25 / Version: 6.0 Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

# Legend

_090	
N/A	Not available
W/W	Weight/Weight
OEL	Occupational Exposure Limit
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
ACGIH	American Conference of Governmental Industrial Hygienists, Inc.
DOW IHG	Dow Industrial Hygiene Guideline

WEEL	Workplace Environmental Exposure Level
HAZ_DES	Hazard Designation
VOL/VOL	Volume/Volume

Americas Styrenics LLC urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.