



Notes:

1. Material: RoHS compliant 12AWG (0.08") Aluminum
2. Break all sharp edges and mask all threads prior to powder coat.
3. Part is to be powder coated with Cardinal color C241-BK109.
Thickness of coating must be between 0.05mm and 0.12mm.
4. Ink mark in area indicated with first initial of your company name.

Rev	Date	Description
F	8/16/16	Thickness of powder coat specification changed.
E	7/27/16	Countersink removed from 2 masked holes for manufacturability.
D	7/6/16	FreeCAD redraw. Masking added to countersunk holes (page 2)

DRAWN BY: bam	DATE: 7.6.16
MATERIAL: See Notes	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS. TOLERANCES ARE:	
DECIMALS .X±.75 .XX±.25 .XXX±.125 .XXXX±.050	ANGLES X°±1° 63°
BREAK EDGES 0.1/0.5 FILLET RADIUS 0.1/0.5	

 ALEPH OBJECTS INCORPORATED		626 West 66th Street Loveland, Colorado 80538, USA Phone +1-970-377-1111 www.alephobjects.com	
		TITLE Right side mini	
SIZE A	DWG NO. PP-FP0052-revF	REV. F	
SCALE 1:3	DO NOT SCALE DRAWING	SHEET 1 of 2	